



BORMA WACHS[®]

Wood Professional Cosmetics



Technical Data Sheet

REV 01 of 17.03.2016

SHINE DECOR GOLD LACK

Gold – for interiors

DESCRIPTION:

Special extra-bright finish, which reproduces the traditional colors of gilding. Finishing varnish of excellent quality and intense decorative effect for the reproduction of gilding, easy to apply and excellent result.

SHINE DECOR GOLD LACK is not over-paintable, although a light fixing overcoat is possible; it is suitable for decorative purposes and is addressed to both the private individual and the craftsman who preferably perform brush applications. It is suitable for the decoration of fine objects, frames, furniture and in general for surfaces in wood, plaster, metal and wall if not subjected to abrasion.

For alternative gilding, for finishing purposes, use GOLD LACK PRO for indoors or GOLDLACK EXTERIORS.

CHEMICAL-PHYSICAL CHARACTERISTICS:

Appearance:	liquid
Available colours:	Rich Gold, Rich Pale Gold, Pale Gold, Ducat Gold, Gold Chrome, Silver Chrome
Odour:	Typical
Temperature of usage:	+10 °C / +35 °C
Drying time:	dust free ≈ 10 min tack free ≈ 60-70 min complete drying ≈ 5 hrs
RH:	< 75%
Yield:	≈ 10-12 m ² /Lt per coat
Dilution:	ready for use
Cleaning:	mineral white spirit o Solvoil 06

METHOD OF USAGE:

Mix the product well before and during use: the dispersed metal powders tend to settle due to their weight.

The product can be applied by brush or spray. Greater homogeneity is obtained by spray application.

On a smooth surface, clean and free of oils, greases, waxes, silicones and old paints, properly sanded and treated with a special primer (for metal: anticorrosive primer; for wood: acrylic, polyurethane, nitro provided that they are silicone-free; for plaster or wall: any insulating base), apply Shine Decor Gold Lack in one or more coats.

By brush/handroller

Recommended for small decorations and details.

Apply in one or more coats. Avoid crossing the direction of the brush stroke in order not to compromise the uniformity of the finish. Wait until completely dry.

By spray

Recommended for maximum uniformity and for large surfaces.

Apply the appropriate amount in one or more coats according to the desired final effect. Wait until completely dry.

STORAGE:

Store in a cool, well-ventilated place, keep container closed when not in use.

Keep away from heat, open flames, sparks and other sources of ignition.

PACKAGING:

The product is available in 125 ml, 375 ml and 750 ml containers.

WARNING:

For professional use only.

Check compatibility (color, resin and oil content) with unknown woods.

Completely remove any residual from previous treatments.

Always check the room temperature and humidity of the wood.

Protect from direct exposure to sunlight and from the air at least for the first 3 hours after application.

Our technical data sheets are drawn up on the basis of the average results of our tests.

However our technical advice is given in good faith but without guarantee.

In fact, different supports, application conditions, systems, dilutions are an integral part of the final result and often beyond any control. The user must try the products supplied to check if they are suitable for his needs.

On our part, the continuity of the chemical-physical characteristics is guaranteed.