

TECHNICAL DATA SHEET

FIRWIN S3 SRA

Safety shoes

Article NO: G3131

Upper: buffalo leather Liner: synthetic fur, foam


Sole: PU2D

Description: full-leather high shoes

steel toecap and midplate

water resistance, with fur lining

Size: 36 - 48



This shoes are suitable for use at building and heavy engineering.

Type and degree of protection:

Category	EN ISO 20345
Antistatic properties	х
Absorption of energy in the heel area	х
Sole with pattern- oil resistance	х
Water resistance	х
Puncture resistance (steel insole)	х
Safety toecap for toe protection	х
Slip resistance on ceramic tile floor with SLS (SRA mark).	х















This personal protective equipment is in conformity with this harmonized European Standard:

EN ISO 20345:2011 - Personal protective equipment - safety shoes. Slip resistance on ceramic tile floor with SLS (SRA mark).



Certified by notified body no. 2369 (VIPO, Slovakia), Certificate number 00125/111/1/2018.

Pairs in carton: 10
Carton weight: 19 kg
Carton size: 0,108 m³
Country of origin: China

The shoes have to be perfect as for from and size, because they have rigid parts. The right size has to be found by measuring practically and carefully the shoes. The closing system has to be used correctly. The laces have to be tightened well without leaving too long free tops. The shoes have to be cleaned and treated with right, specific products, following the instructions for use. Do not keep footwear near heatings when not used and let them dry in a windy or room temperature. Before wearing and when cleaned, the shoes have to be controlled in order to find out visible defects existing, like closing system function, outsole profile's water, possible damages, etc. To define the right type of footwear to wear in every environment, the possible dangers and the place/ environment have to be indeded (e.g. construction industry, high temperatures, etc.). The shoes have to be stored correctly, keeping them in the proper packing.