

Fisa tehnica boiler pentru pompa de caldura cu serpentina marita FORNELLO SOL HP 200 LT 1S

Specificatii	UNIT	200 Litri	300 Litri	500 Litri
Diametru Exterior (cu izolatie)	mm	600	700	700
Diametru interior (fara izolatie)	mm	500	600	600
Inaltime	mm	1240	1270	2080
Conexiune (racord) apa rece/calda	inch	3 / 4 "	1 "	1 "
Conexiune (racord) intrare /iesire serpentina	inch	1 1/4 "	1 1/4 "	1 1/4 "
Conexiune (racord) senzor	inch	1 / 2 "	1 / 2 "	1 / 2 "
Conexiune (racord) Recirculare	inch	3 / 4 "	1 "	1 "
Diametru serpentinei	mm	1 "	1 "	1 "
Suprafata serpentina	m ²	2,01	3,17	4,23
Flansa curatare	inch	4"	4"	4"
Conexiune (racord) rezistenta	inch	1 1 / 4 "	1 1/4"	2 "
Conexiune (racord) Termomanometru	inch	1 / 2 "	1 / 2 "	1 / 2 "
Presiune de lucru	bar	10	10	10
Presiune maxima de lucru	bar	13	13	13
Clasa Energetica		C	C	C
Tip Izolatie		Hard Polyurethane-44 kg/m ³ -50 mm		
Grosime Strat Emailat		Enamel Coating and 250-450 micron		
Garantie		2 Ani		
Element de preservare		Anod de Magneziu		



