

BAUTECH GD-KNG+EV-80

KIT DETECTIE GAZ NATURAL (DETECTOR + ELETROVALVA ¾")

Protectia locuintei impotriva scurgerilor periculoase de gaz metan

Avantaje

- Senzor de inalta performanta
- Dimensiuni si masa reduse
- Metode multiple de instalare, la optiunea utilizatorului



Caracteristici tehnice:

Model:	GD-KNG
Gaz detectat :	CH ₄ / Gaz metan
Tensiune de lucru:	AC 220 V±15%
Putere consumata	Consum Putere Statica<0.3W,
Temperatura de lucru	-10°C~55°C
Mediu ambiant:	Temperatura: 0 °C - + 40 °C Umiditate: <93%RH Fara condens Presiune ambient 86kPa~106kPa
Timp de raspuns:	≤30s Autorevenire
Domeniu detectie	0~20%LEL
Valoare de alarmare	10% LEL
Sunet alarmare	>85dB (1m)
Metode de alarmare	Audio si Vizual
Functionalitati	optional electrovalva sau iesire releu
Masa	240g
Dimensiuni	Lxl×h,mm: 150×60×120
Durata de viata senzor	>5 ani
Senzor	Semiconductor
Grad Protectie	IP30
Acuratete	Conform EN50291/2018

Model:	EV-80 ¾"
Gaz :	GAZ METAN/ GPL
Tensiune nominala	9V -12 V cc impuls
Tensiune de lucru:	9V cc
Temperatura de lucru	-10 °C - +60 °C
Presiune de lucru	0,5-100kPa
Mediu ambiant:	Temperatura: -10°C~55°C Umiditate: <95%RH Fara condens
Timp de raspuns:	<0,3s Raspuns automat
Masa	250 g
Dimensiuni	125x55x95 mm:
Acuratete	Conform EN50291/2018
Model supapa	Normal deschis
Diametru racord valva	3/4" (inch)
Grad protectie	IP54

Dimensiuni kit: 150 x 200 x70 mm

Masa kit: 490 g

