

BAUTECH UPS-LT 2000 VA/24V

SURSA DE ALIMENTARE, NEINTRERUPTIBILA, CU AUTONOMIE RIDICATA (2000 VA)

PRODUS 4 in 1

- SURSA NEINTRERUPTIBILA
- INVERTOR CU UNDA SINUSOIDALA PURA
- STABILIZATOR AUTOMAT DE TENSIEUNE
- INCARCATOR BATERIE DE CAPACITATE MARE



Model Aparat	UPS-LT 2000 VA
Tensiuni de intrare (alimentare) retea	145-275VAC
Tensiune acumulator	24 V (2x12 V, legate in serie)
Putere max. de lucru consumator	1200 W
Frecventa intrare	50 Hz
Tensiune de iesire	230 VAC
Precizia tensiunii de iesire	Mod baterie : $\pm 5\%$; Mod retea: $\pm 8\%$
Frecventa de iesire	Mod baterie: 50Hz $\pm 1\%$; Mod retea sincronizat cu frecventa de intrare
Forma undei de iesire	Unda sinusoidala pura
Eficienta	Mod baterie: $> 75\%$; Mod retea: $> 95\%$
Timp de transfer	$< 4\text{ms}$
Display	Ecran Digital Colorat LED
Protectie	Suprasolicitare incarcare/descarcare, Supraincalzire, Supratensiune, Scurt circuit
Alarma	Mod baterie, tensiune scazuta a bateriei, suprasarcina, supraincalzire, alte erori
Compatibil cu generator	DA
Standard de siguranta	CE(EMC+LVD), IEC 62040
Temperatura ambient	-10°C - $+40^{\circ}\text{C}$
Umiditate ambient	10-90%, fara condens
Zgomot	$< 56\text{dB}$, la 1m distanta si incarcare totala
Dimensiuni (mm)	160x240x390
Masa (kg)	21,4

