

FISA TEHNICA

Derulator cu tambur – 392.225

<i>Date tehnice:</i>	
Foto produs:	
Tip prize:	Schuko cu dublu contact lateral de protectie, 250V~, 16A, IP20
Numar prize:	4 prize cu protective pentru copii
Material carcasa:	Tambur material plastic, cu cadru de metal
Montaj semicarcasa:	Cu suruburi autofiletante nedemontabile
Tip cordon de alimentare:	H05VV-F 3G1,5mm ²
Culoare cordon de alimentare:	Oranj
Lungime cordon de alimentare:	25m, toleranta ± 1%
Tip fisa (stecher):	Schuko injectat cu dublu contact lateral de protectie, 250V~, 16A, IP20
Culoare fisa (stecher):	Negru,
Mod de intrerupere a alimentarii:	Protectie termica
Gradul de protectie:	IP20
Temperatura:	-5°C - +40°C
Protectie:	
<i>Produsul va fi utilizat la urmatoorii parametrii:</i>	
Tensiune electrica	U _{max.} =230V~
Intensitate curent	Rulat - I _{max.} = 4A, Derulat – I _{max.} =10A
Puterea electrica	Rulat - P _{max.} =920W, Derulat - P _{max.} =2300W
Frecventa	50 Hz – 60 Hz
<i>Mod ambalare:</i>	
Individual:	
Colectiv:	
<i>Produsul este in conformitate cu:</i>	
Standardele : SR EN 61316	

Data: 17.04.2014	Intocmit:
Rev.	Alexandru Tutuianu