

FISA TEHNICA

330.104R – Multipriza Connectus 6 x Schuko, protectie la supratensiune, cordon 2,0m, Schuko	
<i>Date tehnice:</i>	
Foto produs:	
Tip prize:	Schuko cu dublu contact lateral de protectie, 250V~, 16A
Numar prize:	6 prize cu protectie pt. copii
Material carcasa:	Plastic
Culoare carcasa:	Argintiu
Montaj semicarcasa:	cu suruburi autofiletante nedemontabil
Tip cordon de alimentare:	H05VV-F 3G1.5mm ²
Culoare cordon de alimentare:	Negru
Lungime cordon de alimentare:	2.0m, toleranta ± 10%
Tip fisa (stecher):	Schuko injectat la 90°, 250V~, 16A
Culoare fisa (stecher):	Negru
Mod de intrerupere a alimentarii:	Intrerupator bipolar basculant
Gradul de protectie:	IP20
Temperatura:	-5°C - +40°C
<i>Produsul va fi utilizat la urmatoorii parametrii:</i>	
Tensiune electrica	U _{max} .= 250V~
Intensitate curent	I _{max} .= 16A
Puterea electrica	P _{max} .= 3600W
Fregventa	50 Hz – 60 Hz
Protectie	Tip protectie SPD Typ3 Protectie la scurtcircuit: 6,5kA Tov-Rezistenta UT/tT = 400V, 5s Nivel de protectie garantat: L-PE, N-PE, L-N <1.8kV, Timp de reactie a protectiei < 25ns
<i>Mod ambalare:</i>	
Individual:	Cu banderola Bachmann, cartonasa cu "prot. pt copii", cartonasa "Overvoltage", eticheta autoadeziva "Engineered in Germany", instructiuni de utilizare si date tehnice
Colectiv:	20 buc, in cutie colectiva de carton
<i>Produsul este in conformitate cu:</i>	
Standardele : SR HD 21.5 S3; DIN EN 61643-11:202-12 + A11:2007, SR EN 60799:2002,	

Data: 02.03.2012	Intocmit:
Rev.	Capilnean Casian