

FISA TEHNICA TUB FLEXIBIL METALIC rev04/2023

INFORMATII TEHNICE COPEX METALIC

COD	DIAMETRU INTERIOR	DIAMETRU EXTERIOR	U.M.	LUNGIME	AMBALARE	CULOARE
MU-TS.9M	9 mm	12,10 mm ±5%	M	50	50	GRI METALIC
MU-TS.11M	11 mm	14,10 mm ±5%	M	50	50	GRI METALIC
MU-TS.14M	14 mm	17,10 mm ±5%	M	50	50	GRI METALIC
MU-TS.16M	16 mm	19,10 mm ±5%	M	50	50	GRI METALIC
MU-TS.18M	18 mm	21,10 mm ±5%	M	50	50	GRI METALIC
MU-TS.21M	21 mm	24,10 mm ±5%	M	50	50	GRI METALIC
MU-TS.26M	26 mm	29,10 mm ±5%	M	25	25	GRI METALIC
MU-TS.32M	32 mm	35,10 mm ±5%	M	25	25	GRI METALIC
MU-TS.37M	37 mm	41,10 mm ±5%	M	25	25	GRI METALIC
MU-TS.42M	42 mm	45,10 mm ±5%	M	25	25	GRI METALIC
MU-TS.50M	50 mm	53,10 mm ±5%	M	25	25	GRI METALIC
MU-TS.60M	60 mm	63,00 mm ±5%	M	25	25	GRI METALIC



DESCRIERE:

ESTETIC SI FLEXIBIL, PROTEJEAZA CABLURILE DE PRAF, ULEI ETC. CONFECTIONAT DIN BANDA DE OTEL PRE-ZINCATA

REZISTENT LA DETERIORARI MECANICE. REZISTENT LA TEMPERATURE AMBIENTIALA :-15 °C /+60 °C

INFORMATII TEHNICE COPEX METALIC CU IZOLATIE PVC

COD	DIAMETRU INTERIOR	DIAMETRU EXTERIOR	U.M.	LUNGIME	AMBALARE	IZOLATIE / CULOARE
MU-TS.9IP	9 mm	13,20 mm ±5%	M	50	50	PVC NEGRU
MU-TS.11IP	11 mm	15,20 mm ±5%	M	50	50	PVC NEGRU
MU-TS.14IP	14 mm	18,40 mm ±5%	M	50	50	PVC NEGRU
MU-TS.16IP	16 mm	20,40 mm ±5%	M	50	50	PVC NEGRU
MU-TS.18IP	18 mm	22,40 mm ±5%	M	50	50	PVC NEGRU
MU-TS.21IP	21 mm	25,40 mm ±5%	M	50	50	PVC NEGRU
MU-TS.26IP	26 mm	30,40 mm ±5%	M	25	25	PVC NEGRU
MU-TS.32IP	32 mm	36,40 mm ±5%	M	25	25	PVC NEGRU
MU-TS.37IP	37 mm	42,40 mm ±5%	M	25	25	PVC NEGRU
MU-TS.42IP	42 mm	46,40 mm ±5%	M	25	25	PVC NEGRU
MU-TS.50IP	50 mm	54,40 mm ±5%	M	25	25	PVC NEGRU
MU-TS.60IP	60 mm	65,00 mm ±5%	M	25	25	PVC NEGRU



DESCRIERE:

ESTETIC SI FLEXIBIL, PROTEJEAZA CABLURILE DE PRAF, ULEI ETC. CONFECTIONAT DIN BANDA DE OTEL PRE-ZINCATA CU PVC.

REZISTENT LA DETERIORARI MECANICE. REZISTENT LA TEMPERATURA AMBIENTIALA :-15 °C /+60 °C

PRODUCATOR : SPOT ELEKTRIK TURCIA