

		A++
(BTU) CAPACITATE RACIRE		12000 (5949103005299/ 5949103005305)
(Ph-V-Hz)SURSA ALIMENTARE		1-220-240/50
MOD		RACIRE                      INCALZIRE
CAPACITATE		3500W(300W~3800W)      3500W(300W~3900W)
(W) INTENSITATE PUTERE		1100W(150W~1400W)      1000W(150W~1270W)
(A) INTENSITATE CURENT		5.0A(0.8A~6.9A)              4.5A(0.8A~6.2A)
EFICIENTA ENERGETICA (W/W)		3,18                                  3,50
EFICIENTA SEZONIERA (W/W)		6,1                                      4
CLASA ENERGETICA RACIRE/INCALZIRE		A++                                  A+
CLASA ENERGETICA		A+++
MOD CONTROL DEBIT REFRIGERANT		TUBURI CAPILARE
COMPRESOR	MODEL	CS-35V3G-1C170AM2A/ CS-35V3G-1C170AM2A-W3
	TIP	ROTATIV
	MARCA	GMCC
UNITATE INTERNA	(m <sup>3</sup> /h) VOLUM AER CIRCULAT	≥600m <sup>3</sup> /h
	(High)(mm) DIMENSIUNI NETE (L*W*H)	780×276×202
	(High)(mm) DIMENSIUNI BRUTE (L*W*H)	855×340×275
	(Kg) GREUTATE NET/BRUT	9/11
	(dB/A) NIVEL PRESIUNE ACUSTICA	22~40
	(dB/A) NIVEL PUTERE ACUSTICA	32~50
UNITATE EXTERNA	(High)mm DIMENSIUNI NETE (L*W*H)	720x298x473
	(High)mm DIMENSIUNI BRUTE (L*W*H)	777×333×530
	(Kg) GREUTATE NET/BRUT	19/22
	(dB/A) NIVEL PRESIUNE ACUSTICA	51
	(dB/A) NIVEL PUTERE ACUSTICA	61
	TIP AGENT RACIRE / CANTITATE	R32/490g
	MOD DEZGHETARE	Auto
CLASELE CLIMATICE	T1	
CONDUCTE FREON	(mm) LICHID/GAZ/LUNGIME	φ6+φ9×3000
	(mm)LUNGIME MAXIMA/DIFERENTA MAXIMA DE NIVEL	15/5



# CHIGO