

		A++	
(BTU) CAPACITATE RACIRE		24000(5949103005329)	
(Ph-V-Hz) SURSA ALIMENTARE		1-220-240/50	
MOD		RACIRE	INCALZIRE
(W) CAPACITATE		6500W(600W~6600W)	6500W(600W~6800W)
(W) INTENSITATE PUTERE		2000W(210W~2180W)	1850W(210W~2050W)
(A) INTENSITATE CURENT		9.2A(1.2A~10A)	8.5A(1.2A~9.4A)
EFICIENTA ENERGETICA (W/W)		3,60	3,70
EFICIENTA SEZONIERA (W/W)		6,1	4
CLASA ENERGETICA RACIRE/INCALZIRE		A++	A+
CLASA ENERGETICA			A+++
MOD CONTROL DEBIT REFRIGERANT		TUBURI CAPILARE	
COMPRESOR	MODEL	KTN150D42UFZ	
	TIP	ROTATIV	
	MARCA	GMCC	
UNITATE INTERNA	(m3/h) VOLUM AER CIRCULAT	≥1000m3/h	
	(High)(mm) DIMENSIUNI NETE (L*W*H)	950×313×240	
	(High)(mm) DIMENSIUNI BRUTE (L*W*H)	1045×403×327	
	(Kg) GREUTATE NET/BRUT	14/17	
	(dB/A) NIVEL PRESIUNE ACUSTICA	32-44	
	(dB/A) NIVEL PUTERE ACUSTICA	42-54	
UNITATE EXTERNA	(High)mm DIMENSIUNI NETE (L*W*H)	835×322×546	
	(High)mm DIMENSIUNI BRUTE (L*W*H)	934×382×608	
	(Kg) GREUTATE NET/BRUT	30/33	
	(dB/A) NIVEL PRESIUNE ACUSTICA	55	
	(dB/A) NIVEL PUTERE ACUSTICA	65	
	TIP AGENT RACIRE / CANTITATE	R32/1200g	
	MOD DEZGHETARE	Auto	
	CLASELE CLIMATICE	T1	
CONDUCTE FREON	(mm) LICHID/GAZ/LUNGIME	φ6.0+φ12×4000	
	(mm)LUNGIME MAXIMA/DIFERENTA NAXIMA DE NIVEL	15/5	



CHIGO