



1 CUTIE = 8  = 2,235 m²

LEGNAR
ACOUSTIC

10 dB ΔL_{in}
21 dB

2in1 
INTEGRATED
ACOUSTIC LAYER

PRODUCT SPECIFICATION

SPECIFICATII PRODUS

VALUE / VALOARE

Floor type		Click floor with acoustic layer / Pardoseala cu click si substrat integrat
Dimensions	Dimensiuni	1220 x 229 mm
Total thickness	Grosime totala	4,0 + 1,3 mm
Wear layer thickness	Grosime strat de uzura	0,55 mm
Quantity of panels in the package	Numar de placi in pachet	8 pcs (2,235 m ²) / 8 buc. (2,235 m ²)
Quantity of package in the pallet	Numar de pachete in palet	42 pcs (93,870 m ²) / 42 buc. (93,870 m ²)
Warranty (the household indoor use)	Garantie (utilizare in interior)	15 years / 15 ani
Installation	Instalare	Click: 5G Vălinge
CE	CE	EN 14041:2004/AC:2006
DoP	DoP	RF40055/13
Customs tariff number	Numar tarif vamal	39181090

TECHNICAL PARAMETERS

PARAMETRI TEHNICI

NORM / NORMA

VALUE / VALOARE

Class of use RESIDENTIAL	Clasa de trafic - REZIDENTIAL	EN ISO 10874	23 (hall, kitchen, living room, dining room) / 23 (hol, bucatarie, sufragerie, living)
Class of use COMMERCIAL	Clasa de trafic - COMERCIAL	EN ISO 10874	33 (shopping centres, schools, large-area offices, halls) / 33 (centre comerciale, birouri largi, hale)
Reaction to fire	Reactia la foc	EN 14041 (EN 13501)	Bfl-s1
Dimensional stability	Stabilitate dimensionala	EN ISO 23999	≤0,05% (norm ≤0,25%) / ≤0,05% (norma ≤0,25%)
Wear resistance	Rezistenta la uzura	EN 13329 Annex E	≥7000 (norm ≥2000) / (norma ≥2000)
Residual indentation	Indentare reziduala	EN ISO 24343-1	≤0,02 mm (norm ≤0,10 mm) / ≤0,02 mm (norma ≤0,10 mm)
Castor chair resistance	Rezistența la testul Castor chair	ISO 4918	Type W >25000 cycles (no damage on wear layer, no stratification) / Tip W 25000 cicluri (fara deteriorari pe stratul de uzura, fara stratificari)
Resistance to large ball	Rezistenta la minge mare	ISO 24334	1800 mm (norm 1600 mm) / (norma 1600 mm)
Locking strength	Rezistenta clic	EN ISO 10582 Annex D	long edge 4,5 kN/m, short edge 5,5 kN/m latura lunga 4,5 kN/m, latura scurta 5,5 kN/m
Slip resistance	Rezistenta la alunecare	EN 13893 / DIN 51130	DS/R9
Antistatic and electrical properties	Proprietati antistatice si electrice	EN 14041 (EN 1815)	<2kV
Resistance to stain and chemicals	Rezistenta la pete si chimicale	EN ISO 26987	INDEX 0 (very good) / INDEX 0 (foarte bun)
Light fastness	Rezistenta la lumina	EN ISO 105-B02	≥6
Thermal resistance	Rezistenta termica	EN 12667	0,042 m ² k/W
Underfloor heating	Incalzire in pardoseala	EN 12524	yes (max 27°C) / da (max 27°C)
IS - Impact sound improvement (integrated acoustic underlay)	IS - Imbunatatirea sunetului de impact (substrat acustic integrat)	EN ISO 717-2	ΔLw = 21 dB
Formaldehyde emission	Emisia de formaldehide	EN 717-1	Class E1
Substances of Very High Concern	Substante deosebit de periculoase	EN 717-1	SVHC free
VOC	COV		A+

LOGISTIC PARAMETERS / PARAMETRI LOGISTICI

	Packaging Unit / Unitatea de ambalare	Pallet / Palet
Form / Forma	Box / Cutie (2,235 m ²)	93,870 m ²
Weight / Greutate	18,63 kg +/- 10%	820 kg +/- 10%
Sizes / Dimensiuni	1234 x 240 x 46 mm	1260 x 750 x 800 mm

CE
23
Decora S.A. Ignacego Prądzyńskiego 24a 63-000 Środa Wielkopolska
RF40055/13
EN 14041:2004 1021
Floor coverings for interior use / Pardoseli pentru uz interior
Reactia la foc / Reaction to fire B_f-s1 Rezistenta la alunecare / Slip resistance DS Emisia de formaldehide / Formaldehyde emission E1

OTHER / ALTELE

