



BAUTECH UPS-LT 500 VA/12V

SURSA DE ALIMENTARE, NEINTRERUPTIBILA, CU AUTONOMIE RIDICATA (500 VA)

PRODUS 4 in 1

- SURSA NEINTRERUPTIBILA
- INVERTOR CU UNDA SINUSOIDALA PURA
- STABILIZATOR AUTOMAT DE Tensiune
- INCARCATOR BATERIE DE CAPACITATE MARE



Model Aparat	UPS-LT 500 VA
Tensiuni de intrare (alimentare) retea	145-275VAC
Tensiune acumulator	12 V
Putere max. de lucru consumator	300 W
Frecventa intrare	50 Hz
Tensiune de iesire	230 VAC
Precizia tensiunii de iesire	Mod baterie : $\pm 5\%$; Mod retea: $\pm 8\%$
Frecventa de iesire	Mod baterie: 50Hz $\pm 1\%$; Mod retea sincronizat cu frecventa de intrare
Forma undei de iesire	Unda sinusoidala pura
Eficienta	Mod baterie: $>75\%$; Mod retea: $>95\%$
Timp de transfer	$<4\text{ms}$
Display	Ecran Digital Colorat LED
Protectie	Suprasolicitare incarcare/descarcare, Supraincalzire, Supratensiune, Scurt circuit
Alarma	Mod baterie, tensiune scazuta a bateriei, suprasarcina, supraincalzire, alte erori
Compatibil cu generator	DA
Standard de siguranta	CE(EMC+LVD), IEC 62040
Temperatura ambient	-10°C - $+40^{\circ}\text{C}$
Umiditate ambient	10-90%, fara condens
Zgomot	$<56\text{dB}$, la 1m distanta si incarcare totala
Dimensiuni (mm)	140x180x350
Masa (kg)	5,1

