





Hormann Romania srl str. Complexului nr 15 com Chiajna, Ilfov	Fisa tehnica Usa basculanta GSL	retea DIY						
6/1/2022		caracteristicile produsului oferit						
producator	Hörmann, Germania							
denumire de tip	Usa basculanta Light							
Foaie usa	Foaie tabla otel, suprafata coaja de portocala							
Culoare RAL	RAL 8028 (Maro); RAL 9016 (ALB)							
Elemente siguranta		capacele protectie flexibile (amplasate deasupra bratelor de parghie)						
		sistem de arc multiplu , asigura usa impotriva caderii. Distantele dintre spirele arcurilor este atat de mica , incat nici macar degetele copiilor nu se pot prinde in ele.						
		protectie anti-efractie. Sistemul unic de blocare cu piedica al usilor basculante Hormann fixeaza colturile blatului usii strans pe rama.						
		sina de culisare profilate unic						
Standard de siguranta	EN 13241-1							
Mod de operare standard	maner plastic PVC							
<p>Ex. Dimensiune comanda: 2500x2000mm; 2500x2125mm; 3000x2125mm Dimensiune cadru usa + 105mm latime + 70mm inaltime = dim. totala cu cadru 2605x2070mm /2605x2195mm/ 3105x2195mm</p>								
<p>Dimensiune efectiva foaie usa: - 58mm latime; - 10mm inaltime</p> <p>(ex. dim foaie usa pt.dimensiunea 2500x2000mm= 2442x1990mm; 2500x2125mm = 2442x2115 mm; 3000x2125mm = 2942x2115 mm)</p> <p>Dimensiune gol util : - 140mm latime; - 120mm inaltime (ex. dim. gol util pt. dimensiunea 2500x2000mm = 2360x1880mm 2500x2125mm = 2360x2005mm 3000x2125mm = 2860x2005mm)</p>								
<p>Modalitate montaj: Montaj in gol: + 125mm latime; + 90 mm inaltime</p> <table border="1"> <tr> <td>ex. dim.com: 2500x2000mm</td> </tr> <tr> <td>ex.dim.necesare montaj in gol: 2625mmx2090mm.</td> </tr> <tr> <td>ex. dim.com: 2500x2125mm</td> </tr> <tr> <td>ex.dim.necesare montaj in gol: 2625mmx2215mm.</td> </tr> <tr> <td>ex. dim.com: 3000x2125mm</td> </tr> <tr> <td>ex.dim.necesare montaj in gol: 3125mmx2215mm.</td> </tr> </table>			ex. dim.com: 2500x2000mm	ex.dim.necesare montaj in gol: 2625mmx2090mm.	ex. dim.com: 2500x2125mm	ex.dim.necesare montaj in gol: 2625mmx2215mm.	ex. dim.com: 3000x2125mm	ex.dim.necesare montaj in gol: 3125mmx2215mm.
ex. dim.com: 2500x2000mm								
ex.dim.necesare montaj in gol: 2625mmx2090mm.								
ex. dim.com: 2500x2125mm								
ex.dim.necesare montaj in gol: 2625mmx2215mm.								
ex. dim.com: 3000x2125mm								
ex.dim.necesare montaj in gol: 3125mmx2215mm.								
<p>Montaj in spatele golului: dim. de comanda = dim. necesara montaj in spatele golului (diferente permise pentru montajul in spatele golului: max. - 30 mm/ max. + 90 mm latime; max. - 30 mm/ max. + 30 mm inaltime; ex.pt.2500x2000mm (2470 -2590mm latime) X (1970 -2030mm inaltime) ex.pt.2500x2125mm (2470 -2590mm latime) X (2095 -2155mm inaltime) ex.pt.3000x2125mm (2970 -3090mm latime) X (2095 -2155mm inaltime)</p>								
Izolatie (optional)	max. 1 kg/ m ² ; grosime izolatia: max 16mm.							
durata medie de exploatare	10 ani - usa basculanta							
perioada de garantie	2 ani - usa basculanta;							

