

Detalii Tehnice Lampa solara cu Panou Separat

	QL30W- 100007	QL60W-100008	QL90W-100009	QL120W-100010	QL150W-100011	QL200W-100012	QL300W-100013
Panou solar							
Tip panou	Polycrystalline silicon	Polycrystalline silicon	Polycrystalline silicon	Polycrystalline silicon	Polycrystalline silicon	Polycrystalline silicon	Polycrystalline silicon
Putere panou	6W	12W	15W	22W	25W	28W	50W
Tensiune maxima	6V	6V	6V	6V	6V	6V	6V
Dimensiune panou	16x34 cm	29x35 cm	35x35cm	34x46cm	36x53cm	36x58cm	44x67cm
Lampa solara							
Dimensiuni	33x9x9cm	38x13x6cm	38x13x6cm	50x21x3.5cm	50x21x6cm	50x21x6cm	50x21x6cm
Greutate	2 kg	3.5 kg	3.7 kg	6.3 kg	6.5 kg	7.2 kg	8.9 kg
Led-uri	70 buc-SMD5730	121 buc-SMD5730	181 buc-SMD5730	256 buc-SMD5730	288 buc-SMD5730	432 buc-SMD5730	671 buc-SMD5730
Putere	30W	60W	90W	120W	150W	200W	300W
Flux luminos	3000 lm	6000 lm	9000 lm	12000 lm	15000 lm	20000 lm	30000 lm
Temperatura de culoare	6000-8000k	6000-8000k	6000-8000k	6000-8000k	6000-8000k	6000-8000k	6000-8000k
Acumulator incorporat	6000mAh LiFePO4	12000mAh LiFePO4	18000mAh LiFePO4	22000mah LiFePO	24000mah LiFePO4	40000mah LiFePO	48000mah LiFePO4
Timp descarcare	Pana la 24h	Pana la 24h	Pana la 24h	Pana la 24h	Pana la 24h	Pana la 24h	Pana la 24h
Clasa de protective	IP65	IP65	IP65	IP65	IP65	IP65	IP65
Brat de fixare - L	30 cm	43 cm	45 cm	50cm	50cm	50cm	50cm
Senzor de lumina	Da	Da	Da	Da	Da	Da	Da
Afisaj putere	da	da	Nu	Da	Da	Da	Da
Inaltime instalare	3-5m	3-6m	4-6m	4-6m	4-6m	4-6m	4-6m



Simbolul indica faptul ca produsul nu trebuie aruncat ca deșeu nesortat, ci trebuie trimis la centre separate de colectare in vederea recuperarii si reciclarii.

Distribuitor: QL Lighting Solution / RO39782018/ office@qlsolution.com



CE RoHS