

FORNELLO BOILER DE SOL CU DOUA SERPENTINE	UNITATE	160	200	300	400	500	800	1000	1500	2000	2500	3000
CAPACITATE	LT	163	205	302	403	505	802	1006	1505	2002	2503	2935
DIAMETRU INTERIOR	MM	450	500	600	600	600	750	850	1100	1100	1200	1250
DIAMETRU EXTERIOR	MM	510	560	660	660	660	850	950	1200	1200	1300	1350
INALTIME	MM	1300	1300	1300	1740	2090	2240	2240	1960	2360	2580	2600
DIMENSIUNE PALET	MM	510X510	560X560	660X660	660X660	660X660	950X950	950X950	1200X1200	1200X1200	1300X1300	1350X1350
GREUTATE BRUTA	KG	82	94	128	165	213	283	315	394	472	505	530
INTRARE APA RECE	INCH	3/4	3/4	1	1	1	1 1/4	1 1/4	1 1/4	1 1/4	2	2
IESIRE APA CALDA	INCH	3/4	3/4	1	1	1	1 1/4	1 1/4	1 1/4	1 1/4	2	2
CIRCULATIE	INCH	3/4	3/4	1	1	1	1 1/4	1 1/4	1 1/4	1 1/4	2	2
INTRARE SERPENTINA PRINCIPALA APA CALDA (SUS)	INCH	1	1	1 1/4	1 1/4	1 1/4	1 1/4	1 1/4	1 1/4	1 1/4	1 1/4	1 1/4
IESIRE SERPENTINA PRINCIPALA APA RECE (SUS)	INCH	1	1	1 1/4	1 1/4	1 1/4	1 1/4	1 1/4	1 1/4	1 1/4	1 1/4	1 1/4
SUPRAFATA DE INCALZIRE SERPENTINA PRINCIPALA (SUS)	M2	0.3	0.35	0.6	0.9	1.3	1.4	1.47	1.6	2.25	2.95	3.31
INTRARE SERPENTINA SECONDARA APA CALDA (JOS)	INCH	1	1	1 1/4	1 1/4	1 1/4	1 1/4	1 1/4	1 1/4	1 1/4	1 1/4	1 1/4
IESIRE SERPENTINA SECONDARA APA RECE (JOS)	INCH	1	1	1 1/4	1 1/4	1 1/4	1 1/4	1 1/4	1 1/4	1 1/4	1 1/4	1 1/4
SUPRAFATA DE INCALZIRE SERPENTINA SECONDARA (JOS)	M2	0.5	0.6	0.8	1.2	1.98	2.78	3.18	2.65	5.3	4.6	4.76
SUPRAFATA TOTALA DE INCALZIRE A SERPENTINELOR	M2	0.8	0.95	1.4	2.1	3.28	4.18	4.65	4.25	7.55	7.55	8.07
CONECTAREA ANODULUI	INCH	1 1/4	1 1/4	1 1/4	1 1/4	1 1/4	1 1/2	1 1/2	1 1/2	1 1/2	1 1/2	1 1/2
RACORDARE REZISTENTA ELECTRICA	INCH	1 1/4	1 1/4	1 1/4	1 1/4	1 1/4	2	2	2	2	2	2
GROSIMEA IZOLATIEI	MM	30	30	30	30	30	50	50	50	50	50	50
DENSITATEA IZOLATIEI	KG/M3	44	44	44	44	44	18	18	18	18	18	18
FLANSA DE CURATARE	INCH	4	4	4	4	4	5	5	5	5	5	5