



SPECIFICATII TEHNICE		CAZAN COMBUSTIBIL SOLID FORNELLO ECO ENERGY			
		SERIE / MODEL			
Model	Unitate	WB 25	WB 35	WB 40	WB 50
Putere (kW)	kW	20-25	30-35	35-40	40-50
Suprafata aproximativa incalzita (pana la)	m ²	150	200	250	300
Volum manta de apa din cazan	l	90	105	115	126
Greutatea cazanului	kg	282	322	344	380
Diametrul / Inaltimea cosului de fum	mm	150/980	160/980	180/980	180/970
Dimensiune racord Tur / Retur cazan - (Filet Exterior)	toli	1-1/4"	1-1/4"	1-1/4"	1-1/4"
Dimensiune racord alimentare / golire - (Filet interior)	toli	1/2"	1/2"	1/2"	1/2"
Temperatura maxima de functionare	C	90	90	90	90
Presiunea maxima de lucru	bar	2,5	2,5	2,5	2,5
Adancimea totala a cazanului (A)	mm	1000	1075	1075	1175
Latimea totala a cazanului (B)	mm	488	588	638	638
Inaltimea totala a cazanului (C)	mm	1220	1220	1220	1220
Inaltime racord Tur (D)	mm	1146	1146	1146	1146
Inaltime racord Retur (F)	mm	545	545	545	545