

PSR22	APLICATII
RELEU PORNIRE POMPA	rezidential

CARACTERISTICI FUNCTIONARE

Recomandare instalare : min 4,5m de panoul de comanda al instalatiei de irigat

Certificari : IP44, UL, CE, NEMA3

CARACTERISTICI

- Conductorii de 24V asigura o conexiune rapida si facila
- Potrivit atat pentru cablare conventionala cat si pentru decodoare bifilare
- Potrivit pentru pompe pana la 1.5kW (120V) sau 2.2kW (230V)



DIMENSIUNI

17cm H x 19cm L x 12cm l

Model	Monofazat		Trifazat	Incarcare max.	Rezistenta max.	Bobina V				Bobina V			
	kW la 120V	kW la 230V	kW la 230V	A	A	indus		A		sustinut		A	
						50Hz	60Hz	50Hz	60Hz	50Hz	60Hz	50Hz	60Hz
PSR22	1.5	2.2	-	30	40	33	30	1.38	1.25	8	6.5	0.33	0.27

Lungimea maxima de cablu

Model	PSR22
0.75mm ²	74m
1.5mm ²	118m
2.5mm ²	188m
4mm ²	298m
6mm ²	473m
10mm ²	751m



S.C. INTTECH INDUSTRY SRL

Str. Leonte Filipescu 2, Voluntari / ILFOV

Phone: +40 21 569.04.17

Mobile : +40 757.118.165

Email: inttech@inttech.ro