

VARIOCLIC EXTENSIVE

8mm AC4



Specificatii produs

Dimensiuni				
Dimensiuni	Grosime	8 mm ± 0.50mm; max – min ≤ 0.50mm;		
	Lungime	1203,5 mm ≤0.50mm;		
	Latime	191,7 mm ≤0.10mm; max–min ≤0.20mm;		
Profil	Latura lunga	2G	Latura scurta	2G
Suprafata		Timberland – 4V		
Cantitate				
m²	Pachet	1,8456 m²		
	Palet	110,736 m²		
Placi	Pachet	8 buc		
Tolerante				
Perpendicularitate	EN 13329	≤ 0.20mm		
Rectitudine	EN 13329	≤ 0.30mm		
Planeitate transversal	EN 13329	Concav: ≤ 0.15% Convex: ≤ 0.20%		
Planeitate lungime	EN 13329	Concav: ≤ 0.50% Convex: ≤ 1.00%		
Deschidere intre elemente	EN 13329	Media: ≤ 0.15mm Max: ≤ 0.20mm		
Diferenta inaltime intre elemente	EN 13329	Media: ≤ 0.10mm Max: ≤ 0.10mm		
Test				
Rezistenta abraziune		EN 13329	AC4 (≥ 4000rpm)/Clasa 32	
Rezistenta impact bila mica		EN 13329	≥12N	
Rezistenta la patare	grup 1 + 2	EN 13329	Grad 5	
	grup 3		Grad 4	
Efectul unei role de scaun		EN 13329	25 000 cicluri, fara deteriorari	
Umflare in grosime		EN 13329	≤ 18%	
Rezistenta expunere la lumina		EN 13329	Scala albastra	≥6
			Scala gri	≥4
Mediu				
Emisia de formaldehida		SR EN 12460-3	E1	
Comportament				
Clasificarea reactie la incendiu		EN 13501-1	Cfl-s1	
Rezistenta la alunecare		EN 13893	Clasa tehnica DS	
Rezistenta termica		EN 12667	0.06 (m²K)/W	