

Fișă tehnică Art. 931.250

Data sheet | Fiche technique | Scheda tecnica | Fișa tehnică

TWIST

Parametrii electrici		Electrical parameters	
Curent nominal / tensiune nominală Frecvență	16A / 250V~ 50Hz	Rated current / rated voltage Frequency	16A / 250V~ 50Hz
Racordarea la rețea		Power supply	
Cordon Culoare cordon demontabil	2,0m H05VV-F 3G1,5mm² Negru	Supply cable Colour supply cable Rewireable	2,0m H05VV-F 3G1,5mm² Black
Fisa Cu conectori Cu fisa demontabila, inclusa	CEE 7/7 (Type E/F)	Plug With ferrules With enclosed mounting plug	CEE 7/7 (Type E/F)
Iesire		Power output	
Prize 2x CEE 7/3 (Type F) 2 poli cu contact de împământare Negru, similar cu RAL 9005, 90° 16A 250V~, IP20		Socket outlets 2x CEE 7/3 (Type F) 2-pole with earthing contact With shutter Black, similar to RAL 9005, 90° 16A 250V~, IP20	
Alte caracteristici ale produsului		Further product attributes	
Grosime blat Adancime montaj Platforma	ab 8mm ca. 40mm TWIST	Tabletop thickness Mounting depth Platform	from 8mm ca. 40mm TWIST
Material Carcasa: PA6 GF30 850°C, negru, asemanator RAL9005 Capac: Metal, vopsit în alb similar cu RAL 9010, satin 30GE		Material Housing: PA6 GF30 850°C, black similar to RAL 9005 Cover: Metal, painted in white similar to RAL 9010, semi-matt 30GE	
Montaj Decupaj blat	105 (+1) mm	Mounting Table cut-out	105 (+1) mm
Continut produs		Scope of delivery	

1x TWIST
1x fisa demontabila
1x instrument montaj

1x TWIST
1x Mounting plug
1x Mounting tool

In carton

In carton

Condiții ambientale

Environmental conditions

Temperatura ambiantă în timpul instalării și folosirii. 17°C – 35°C
A se feri de lumina directă a soarelui.

Surrounding temperature during mounting and use 17°C – 35°C
Protect from direct sunlight.

Temperatura ambiantă în timpul transportului și depozitării -25°C - 60C°
Protecție IP20

Surrounding temperature during transport and storage -25°C - 60C°
Protection type IP20

Conformitatea / Approbation

Conformity / Approval

Certificat conform IEC 60884, VDE 0620-1

Certified according to IEC 60884, VDE 0620-1

