

Fișă tehnică Art. 928.017

Data sheet | Fiche technique | Scheda tecnica | Fișă tehnică

ELEVATOR

Parametrii electrici		Electrical parameters	
Curent nominal / Tensiune nominală Frecvență	16A / 250V~ 50Hz	Rated current / rated voltage Frequency	16A / 250V~ 50Hz
Racordarea la rețea		Power supply	
Cordon	2,0m H05VV-F 3G1,5mm²	Supply cable	2,0m H05VV-F 3G1,5mm²
Fisa Cu conectori Cu fisa demontabila, inclusa	CEE 7/7 (Tip E/F)	Plug With wire end ferrules With enclosed mounting plug	CEE 7/7 (Type E/F)
Iesire		Power output	
Prize 1x CEE 7/3 (Type F) 2 poli cu contact de împământare Cu protecție sporită împotriva contactului accidental, Negru, asemanator RAL 9005, 90° 16A		Socket outlets 1x CEE 7/3 (Type F) 2-pole with earthing contact With shutter Black, similar to RAL 9005, 90° 16A 250V~, IP20	
Modul functional		Function modules	
USB-Charger USB Dublu incarcator	3,1A / 5VDC	USB charger Double charger	3,1A / 5VDC
Alte caracteristici ale produsului		Further product attributes	
Grosime blat Adancime montaj Platforma	16-60mm 135mm ELEVATOR	Tabletop thickness Mounting depth Platform	16-60mm 135mm ELEVATOR
Material Carcasa: Aluminiu, aspect de oțel inoxidabil		Material Housing: Aluminium polished Stainless steel look	
Acoperire (superioara): Oțel inoxidabil ștanțat		Cover (Top): Stainless steel brushed and stamped	
Capace prize: PA6 GF30 850°C, negru, asemanator RAL9005		Cover (Socket outlets) : PA6 GF30 850°C, black similar to RAL 9005	

Montaj		Mounting	
Decupare blat	80 (+/- 1mm)	Table cut-out	80 (+/- 1mm)
Continut produs		Scope of delivery	
1x multipriza ELEVATOR		1x Power strip ELEVATOR	
1x fisa demontabila		1x mounting plug	
In carton		In carton	
Conditii ambientale de transport		Environmental conditions	
Temperatura ambiantă în timpul instalării și folosirii		Surrounding temperature during mounting and use	17°C – 35°C
A se feri de lumina directă a soarelui		Protect from direct sunlight	
Temperatura ambiantă în timpul transportului si depozitare		Surrounding temperature during transport and storage	-25°C - 60°C
Protectie	IP20	Protection type	IP20
Conformitate / Approbation		Conformity / Approval	
Certificat dupa	IEC 60884, VDE 0620-1	Certified according to	IEC 60884, VDE 0620-1
WEEE-corespunzator		Underlies WEEE	

